







SUBMITTED OR TRANSMITTED IN COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 800 0 8 AUG 2003
WIPO PCT

BEST AVAILABLE COPY

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the pany to certain additional company law rules.

Signed

Dated


25 July 2003

Agodan Hordley

An Executive Agency of the Department of Trade and Industry

ra | 1/77

Patents Act 1977 (Bule 16)



21 E725385-1 002697 P0 0-00-0214229.7

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road Newport South Wales NP10 800

NP10 8QQ 1. Your reference PA/GS02 Patent application number (The Patent Office will fill in this part) 0214229.7 3. Full name, address and postcode of the or of each applicant (underline all surnames) [see continuation sheet] Patents ADP number (if you know it) If the applicant is a corporate body, give the country/state of its incorporation Title of the invention HAND-SQUEEZABLE DISPENSERS Name of your agent (if you have one) GRAHAM F COLES "Address for service" in the United Kingdom GRAHAM COLES & CO to which all correspondence should be sent 24 SEELEYS ROAD (including the postcode) BEACONSFIELD BUCKINGHAMSHIRE HP9 1SZ Patents ADP number (if you know it) 4361556001 6. If you are declaring priority from one or more earlier patent applications, give the country Country Priority application number Date of filing and the date of filing of the or of each of these (if you know it) (day / month / year) earlier applications and (if you know it) the or each application number 7. If this application is divided or otherwise Number of earlier application derived from an earlier UK application, Date of filing give the number and the filing date of (day / montb / year) the earlier application

8: Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer Yes' if:

a) any applicant named in part 3 is not an inventor, or

- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body. See note (d))

Patents Form 1/77	
9. Enter the number of sheets for of the following items you are filing with this form. Do not count copies of the same document	
Continuation sheets of this form	
Description	8
Claim(s)	
Abstract	
Drawing(s)	6+6 116
10. If you are also filing any of the following, state how many against each item.	
Priority documents	
Translations of priority documents	•
Statement of inventorship and right to grant of a patent (Patents Form 7/77)	
Request for preliminary examinationand-search-(Patents-Form_9/77)_	
Request for substantive examination (Patents Form 10/77)	
Any other documents (please specify)	
11.	I/We request the grant of a patent on the basis of this applicat
e	Signature Date 19-06-
12. Name and daytime telephone number of person to contact in the United Kingdom	GRAHAM F COLES \$ 01494 677181

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

Item 3. Full name, address and postcode of each applicant

MICHAEL CHARLES HORE
12 INKERMAN DRIVE,
HAZLEMERE,
HIGH WYCOMBE,
BUCKINGHAMSHIRE HP15 7JJ

6735385001

ADP No

and

CHRISTOPHER HARTLEY
THE BUNGALOW,
ASHWELL COURT,
WINDSOR LANE,
LITTLE KINGSHILL,
GREAT MISSENDEN,
BUCKINGHAMSHIRE HP16 ODZ

ADP No

8408080001

J. Cles 19-06-02

Hand-Squeezable Dispensers

This invention relates to hand-squeezable dispensers.

Hand-squeezable dispensers are widely used especially for 5 dispensing viscous or semi-viscous liquids, such as shampoos and detergents, but are also used for dispensing powders or other particulates, as well as free-flowing Such dispensers commonly take the form of a resiliently-squeezable bottle or other container of blow-10 moulded plastics material, that is discarded when empty. Since the bottle or other container is often specially configured for aesthetic and tactile appeal, it may represent a significant proportion of the overall cost of the product, so that economic and material wastage is 15 involved together with environmental issues in its Although in some instances, provision is made for re-filling the bottle or other container this is normally from another plastics container that is 20 discarded after use, so that wastage and environmental issues still to some extent remain.

It is one object of the present invention to provide a form of hand-squeezable dispenser by which economic and material wastage and problem of environmental disposal, can be reduced.

According to one aspect of the present invention there is provided a hand-squeezable dispenser comprising a container for liquid or other material to be dispensed, the container being compressible for dispensing the liquid of other material therefrom, and a holder for at least partially enclosing the container, wherein the holder has a resiliently-biased part for compressing the container from its uncompressed condition when the holder is squeezed by hand against the action of the resilient bias, and wherein said part is engaged with the container.

2 such that when the squeezing is relaxed the container returns towards its uncompressed condition under the action of the resilient bias. With the dispenser of the invention it is unnecessary for the container to have any inherent resilience for its return towards the uncompressed condition following squeezing. Accordingly, it may be of material (for example, paper or card, or metal-foil or plastics-film) that is relatively inexpensive and readily bio-degradable so that the economic and other disadvantages of using resilient plastics can be avoided. Furthermore, the

aesthetic and tactile appeal desired, can be more costeffectively invested in the re-useable holder rather than in the disposable bottle- or other container-dispenser of 15

the prior art.

5

10

20

25

30

35

The container of the dispenser of the invention may have an external pocket or other means into which said part of the holder extends to engage the container as aforesaid. The said part may be one of two resiliently-biased limbs which extend either side of the container for bearing on opposed wall-parts of the container when the holder is squeezed by hand, and which are engaged within the pocket or other means (individual or common to the two limbs) for returning the container towards its uncompressed condition when the squeezing is relaxed.

According to another aspect of the invention there is provided a holder for at least partially enclosing a compressible container of liquid or other dispensable material, to form a hand-squeezable dispenser, wherein the holder has a resiliently-biased part which is handsqueezable onto the container against the resilient bias, for compressing the container from its uncompressed condition, and which is engageable with the container for returning the container towards its uncompressed

condition under the action of the resilient bias when the squeezing is relaxed.

A squeezable dispenser in accordance with the invention will now be described, by way of example, with reference to the accompanying drawings, in which:

Figure 1 is a perspective view of the hand-squeezable dispenser of the present invention;

10

20

Figures 2 is a perspective view of a container of viscous or semi-viscous liquid, forming part of the hand-squeezable dispenser of Figure 1;

Figure 3 is illustrative of the folded construction of the container of Figure 2;

Figure 4 is a perspective view of a frame or holder for receiving the container of Figure 2, in the assembled hand-squeezable dispenser of Figure 1;

Figure 5 is illustrative in partly broken-away form, of a lower part of one of two limbs of the holder of Figure 4;

Figures 6 and 7 are perspective views illustrating successive stages of assembly of the hand-squeezable dispenser of Figure 1.

Referring to Figure 1, the hand-squeezable dispenser is for dispensing a viscous or semi-viscous liquid such as a detergent, and consists of a rectangular compressible container 1 holding the liquid, and a moulded-plastics frame or holder 2 having an inverted-U configuration, for partially enclosing the container 1.

35

The container 1, which is illustrated in Figures 2 and 3, is of a folded-paper or -card box-construction having an

internal wax-coating or liquid-proof membrane for retaining the liquid to be dispensed; where a membrane is used it may be of plastics- or metal-film bonded as a backing to the paper or card. The folding, as illustrated more especially in Figure 3, defines the top and bottom walls 3 and 4 of the container 1 as extending from upper and lower circumferential double-fold sections 5 and 6 respectively, that both overlap the front and back walls 7 and 8 and the two side walls 9 and 10 of the container 1. Bonds are formed (by glue or otherwise) within both folds of the section 5 so that a firm, circumferential shoulder 11 is established at the upper end of the container 1. No such bonds are formed within the folds of the section 6 (or at least within the inner fold) so that an upwardly-open circumferential pocket 12 is established at the lower end. A ring 13 that defines an outlet for the liquid is inset centrally into the top wall 3; the outlet remains closed by a membrane seal 14 that extends across the ring 13, until the container 1 is activated for use within the holder 2.

Referring now also to Figure 4, the holder 2 has two flat-plate limbs 20 and 21 that splay out resiliently from an interconnecting top-section 22; the limb 20 is longer than the limb 21 by virtue of an extra, bottom blade-section 23 of reduced thickness. The top-section—22 has a transverse cap or lid 24 which is hinged resiliently to the limb 21 and is held open by a finger 25 that projects from a retracted slide 26 mounted on the inside of the limb 21.

As illustrated in Figure 5, the slide 26 is coupled to a horizontal cross-bar 27 on the outside of the limb 21, by two pins 28 that extend through respective vertical slots 29 in the limb 21. With the cross-bar 27 in the position shown in Figures 4 and 5, the pins 28 are at the tops of their slots 29 for retraction of the slide 26 and with

30

35

5

10

15

20

25

the finger 25 obstructing closing of the lid 24. By moving the bar 27 downwardly to take the pins 28 to the bottoms of their slots 29, the slide 26 is extended to project from the bottom of the limb 21 as illustrated in chain-dotted line in Figure 5, and the finger 25 is withdrawn from obstructing the lid 24.

5

25

30

35

Assembly of the dispenser is carried out by placing the holder 2 with its limbs 20 and 21 straddling the upper end of the container 1 and extending down alongside the 10 front and back walls 7 and 8 respectively. The holder 2 is angled to insert the blade-section 23 of the limb 20 in the pocket 12 on the wall 7. It is then pushed down fully to bring the top-section 22 flat onto the top wall 3 of the container 1 and a ridge-projection 30 on the 15 inside of the limb 20, under the shoulder 11 of the front container-wall 7. This brings about the intermediate state of assembly of the dispenser, illustrated in Figure 6, in which the limb 21 remains splayed out resiliently from the back wall 8 of the container 1. 20

In order to complete the assembly of the dispenser, the limb 21 is pushed in towards the back wall 8 and held there by hand, to bring a ridge-projection 31 on the inside of the limb 21 under the shoulder 11 of the wall With the limb 21 held in this condition, the bar 27 is pushed down to extend the slide 26 into the pocket 12 on that wall. This allows the hand-hold on the limb 21 to be released, and withdraws the finger 25 from obstructing closing of the lid 24, so as to bring about the fully-assembled state of the dispenser, illustrated in Figure 7. In this state, the engagement of the bladesection 23 and the extended slide 26 within the pocket 12, and the projections 30 and 31 under the shoulder 11, retains the container 1 front and back, firmly within, and as one with, the holder 2. A detent (not shown) is active resiliently between the slide 26 and the limb 21

6 to restrain the slide 26 in its extended condition and thereby maintain retention of the container 1 within the holder 2. In order to activate the dispenser from the state 5 illustrated in Figure 7, ready for dispensing liquid, the lid 24 is closed down onto the top wall 3 of the container 1; the resilience of its hinging gives the lid 24 a snap action in opening and closing. Closing of the lid 24 brings a sealing cap 32 on the underside of the 10 lid 24 down hard onto the ring 13. A piercing tube 33 of the cap 32 pierces the seal 14, but the cap 32 fits closely onto the ring 13 so that the container 1 remains sealed while the lid 24 is closed. 15 Liquid within the container 1 is dispensed by first snapping the lid 24 open so as to unstop the outlet defined by the ring 13, and then squeezing the limbs 20 and 21 inwardly towards one another while the dispenser is held appropriately inverted. The squeezing of the 20 limbs 20 and 21 inwardly towards one another, applies pressure to the walls 7 and 8 of the container 1 forcing liquid from within the container 1 through the outlet-When sufficient liquid has been dispensed, the squeezing action is relaxed, allowing the limbs 20 and 21 25 to return under the resilient action of their hinging to the top-section 23. The folded-paper or -card construction of the container 1 is such that until it is assembled with the holder 2, it 30 keeps its rectangular form sufficiently to allow it to stand unsupported upright on its bottom wall 4, only while it is full and in its initial, sealed state. the seal 14 has been pierced and the container 1 squeezed to dispense liquid, the container 1 on its own tends to 35 collapse, but when assembled with the holder 2 in accordance with the invention, is afforded rigidity and

is restored to the original rectangular form after squeezing. In the latter respect, the insertion of the blade-section 23 and extended slide 26 in the pocket 12, ensures that the walls 7 and 8 of the container 1 are pulled outwardly, to restore the container 1 to its original shape and to hold it so, as the limbs 20 and 21 move outwardly when the squeezing is relaxed. Once the container 1 has been restored to its original form, the lid 24 is closed, to seal the container 1, until the dispenser is required to be used again.

5

10

15

20

25

30

35

The dispenser can be used repeatedly in the manner described until the container 1 is empty. A refill container of the same construction and initially-sealed form as container 1, is then loaded in the holder 2 in place of the container 1. The empty container 1 is released from the holder 2 by first opening the lid 24, and retracting the slide 26 from the pocket 12 by lifting the bar 27 against the action of the restraining detent. Retraction of the slide 26 moves the finger 25 upwardly to preclude closing of the lid 24, and frees the limb 21 to splay outwardly away from the back wall 8, returning the dispenser to the intermediate state illustrated in The splaying outwardly of the limb 21 releases the projection 31 from under the shoulder 12 so that the container 1 can be withdrawn from between the limbs 20 and 21, disengaging the projection 30 from the shoulder 11 and the blade-section 23 from the pocket 12.

The refill container, and any subsequent container used for refill purposes, is assembled with the holder 2 and used for dispensing, in the same way as the container 1 is assembled and used with it as described above. In each case, the container when loaded in the holder 2 is held firmly by engagement with it of the limbs 20 and 21, and after being squeezed to dispense liquid is returned by them to its original, uncompressed shape under the

resilience of their hinging. Moreover, the holder 2 affords support to the assembly, enabling the dispenser to stand upright on its bottom wall (the wall 4 of the container 1).

Although the container 1 of the dispenser described above, is constructed by folding paper or card, this is not necessarily so, and engagement between the holder 2 and the container 1 may be other than by engagement of the limbs 20 and 21 in a pocket; for example the limbs 20 and 21 may engage under strap elements attached (by glue or otherwise) to the walls 7 and 8 respectively. Furthermore, although the dispenser is described in the context of dispensing viscous or semi-viscous liquid, it may be used for dispensing free-flowing liquid (for example, milk), powder (for example, talcum powder) or particulates (for example, granular salt).

1/6




Fig.1






Fig.2








Fig. 6




Fig. 7

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

BLACK BORDERS
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
☐ FADED TEXT OR DRAWING
BLURRED OR ILLEGIBLE TEXT OR DRAWING
SKEWED/SLANTED IMAGES
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
☐ GRAY SCALE DOCUMENTS
LINES OR MARKS ON ORIGINAL DOCUMENT
REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
□ other:

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.